







Tubi a triplo spessore in acciaio inossidabile per telai da competizione.
 Stainless steel triple butted tubes for competition frames.

new

CODICE CODE	DIMENS. (MM) DIMENS. (MM)	CARATTERISTICHE SPECIFICATIONS	PESO* WEIGHT	TUBO TUBE
XCRL11600 TUBO ORIZZONTALE TOP TUBE	Ø 31.7 L=600 0.6/0.4/0.6	Tondo triplo rinforzo Round triple butted	181 g	
XCRA12670 TUBO OBLIQUO DOWN TUBE	Ø 38 L=670 0.65/0.45/0.65	Tondo triplo rinforzo Round triple butted	260 g	
XCRM13635 TUBO VERTICALE SEAT TUBE	Ø 31.7 L=635 0.7/0.5	Tondo doppio rinforzo Round double butted	221 g	
XCR114TO410 POSTERIORE ORIZZONTALE CHAIN STAY	Ø 24 L=410 0.7/0.5	Rinforzato conificato Butted tapered	106 g	
XCR615560 POSTERIORE VERTICALE SEAT STAY	Ø 16 L=560 0.5	Tondo conificato Round tapered	90 g	
XCRK18600 TUBO STERZO HEAD TUBE	Ø 36 L=600 1.1	Tondo Round	121 g	

*Il peso si riferisce al tubo dimensionato e sgolato per un telaio corsa dimensione 54cm c-c
 *The weight refers to a sized and mitered tube for a 54cm c-c road frame